∢ 46 29 0.025 0.03 □77.5 22 1 12.5 06Ø 17 10 4.50 Ø  $\sim$ 26  $\bigcirc$ Ø70g6(-0.029) Ø22k6(+0.002) Ø21.75<sup>-0.01</sup> Ø80<sup>+0.12</sup> Æ≘∌ 0 15  $\cap$ 22.5 Ø19G6(+0.020) В 4-Ø6.6 11 DIB 4-M6×12 43 M8x20 **DIN 5480 SPLINES** W22x1.25x30x16x6m Note 1: This drawing shows the dimensions of X-Treme-SQ-ST-075 - 2 stages (It is common to all ratios from 12 to 100) Note 2: Smooth shaft version available at no charge, DIN5480 splined shaft version is a paying option Designed by MMI Note 3: This version is using a compact input stage. In case of need for more torque, please select the standard version. Note 4: Full technical ratings can be found on www.reckondrives.com Note 5: Our technical support team can provide accurate data about your specific application at drawing\_request@reckondrives.com ©Reckon Drives, 1, rue Georges GUYNEMER, 42160 ANDREZIEUX - BOUTHEON, FRANCE / contact@reckondrives.com

183

ш

∢

**9**0  $\bigotimes$ 

> Version 1.0 Date: 02-18-2020 X-TREME-SQ-ST-075 2 stages / compact Motor: Siemens 1FK7042